

HS-5nP 5GHz Outdoor System

Built-in 23dBi panel antenna



Key Features

- 4.9~6.1GHz operating frequency
- SISO OFDM modulation
- High gain antenna integrated
- Management Tool
- IP68 enclosure

Specifications

Radio	
Frequency range	4.9~6.1GHz
Channel bandwidth	HT20, HT40
Modulation	SISO, OFDM
Antenna	23dBi plat panel antenna



Output power						
29dBm @ 6Mbps	27dBm @ 54Mbps	30dBm @ HT20	27dBm @ HT40			
Sensitivity						
-89dBm @ 6Mbps	-70dBm @ 54MBps	-65dBm @ HT20	-62dBm @ HT40			
Interfaces						
LAN	10/100 Base-T RJ45 port					
Security						
Data Encryption	WEP, WPA, WPA2					
Advanced	MAC access filter, firewall					
Software functions						
Management & setup	Web-based via popular browser (Chrome, IE 9.0 or later)					
Radio Management	Windows-based tool					
Network architecture	AP, CPE, Bridge					
Protocol	TCP/IP					
SNMP	V1, V2C, V3					
Antenna alignment	N/A					
Power supply & consu	mption					
Power supply	802.3af 48V PoE					
Environment						
Operating temperature	-20 ~ +80° C					
Humidity	10% ~ 95% non-condensing					
Physical						
Dimension	335(L) * 335(W) * 81(H) mm					
Weight	2.9kgs					
Standard accessories						
48v PoE, AC cord, mount	48v PoE, AC cord, mount kit					