



HS-5nP 5GHz Outdoor System

Built-in 23dBi panel antenna



Key Features

- 4.9~6.1GHz operating frequency
- SISO OFDM modulation
- High gain antenna integrated
- Management Tool
- IP68 enclosure

Specifications

Radio			
Frequency range	4.9~6.1GHz		
Channel bandwidth	HT20, HT40		
Modulation	SISO, OFDM		
Antenna	23dBi plat panel antenna		
Output power			
29dBm @ 6Mbps	27dBm @ 54Mbps	30dBm @ HT20	27dBm @ HT40
Sensitivity			
-89dBm @ 6Mbps	-70dBm @ 54Mbps	-65dBm @ HT20	-62dBm @ HT40

Interfaces	
LAN	10/100 Base-T RJ45 port
Security	
Data Encryption	WEP, WPA, WPA2
Advanced	MAC access filter, firewall
Software functions	
Management & setup	Web-based via popular browser (Chrome, IE 9.0 or later)
Radio Management	Windows-based tool
Network architecture	AP, CPE, Bridge
Protocol	TCP/IP
SNMP	V1, V2C, V3
Antenna alignment	N/A
Power supply & consumption	
Power supply	802.3af 48V PoE
Environment	
Operating temperature	-20 ~ +80° C
Humidity	10% ~ 95% non-condensing
Physical	
Dimension	335(L) * 335(W) * 81(H) mm
Weight	2.9kgs
Standard accessories	
48v PoE, AC cord, mount kit	

Provided by Hot Stuff Intl. Co., Ltd.

For more information, contact: service@hotstuff.com.tw